



BRUYNZEEL MULTIPANEL

MULTIGROOVE

OUTDOOR PANELS ► BUILDING AND MARINE



Guarantee

Exterior Carpentry

10 years

DESCRIPTION

Up graded grooved okoume plywood for outdoor applications

USINGS

This product is especially suitable for outdoor panels, cladding, walls, shutters, marine industry requiring varnished or painted finishes

ADVANTAGES

- ✓ Naturally sustainable wood
- ✓ Selected veneers and excellent mechanical resistance
- ✓ 10 years guarantee

COMPOSITION

Face 1 : Okoume rotary cut veneer 15/10° quality I

(I : natural whole piece, no knots, no splits, no rough veneers, very low contrast variation in colour)

Face 2 : Okoume rotary cut veneer 15/10° quality III

(II : natural whole piece or edge glued jointed veneers, small knots/splits allowed, rough veneers excluded)

Inner layers in selected peeled okoume veneers, thin layers (thickness max allowed 20/10°)

(natural whole piece free of defect or edge glued jointed veneers, no split, no overlap, no defect telegraphing through the face veneers)

Grooves : Trapeziod grooves 103 + 10 or 73 + 10

(Assembly by tongues and grooves)

WOOD SPECY

Okoume (500 kg/m3 +/-10%)

GLUING

EN 314-2 : Class 3 (EN 636-3) Exterior using

EN 717-2 : E1 very low formaldehyde emission

SIZES

Regular sizes in mm : 2500x1220

Special sizes in mm : 2150x1242 – 2130x930

THICKNESSES

mm	9
plies	5

Surface finishing sanded 2 faces

For any other thickness and size, please contact us

OPTIONS

Cut at size, CNC milling, varnishing

SAS ALLIN

RUE DE LA COUARDE - F-79270 LE VANNEAU

Tel : +33 5 49 35 00 02 – Fax : +33 5 49 35 02 64

E-mail : allin-sa@allin.fr – Site web : www.allin.fr